



N01a: UC^{FIBRE™} Universal Stranded Loose Tube Cable

Stranded loose tube cable with up to 288 fibres, FireBur® sheath. VDE: U-DQH



OPTIONAL BLACK SHEATH



Application and Installation

This is a Universal indoor/outdoor cable for application as a trunk cable in LAN, MAN and WAN backbones. The cable can be installed ducts and on cable trays. The cable may be installed directly in the ground with proper sand filling.

Standards

EN 187 000, IEC 60794-2, IEC 60794-2-20, IEC 60794-2-21, ISO 11801 2nd edition, EN 50 173-1

Flame Resistance

LSHF (FRNC): IEC 60332-1-2; IEC 60754-1; IEC 60754-2; IEC 61034-2; Class E_{ca}

Options

As standard this cable is provided with 12 fibres per tube, as an option other lower fibre counts are possible

N01a: UC^{FIBRE™} Universal Stranded Loose Tube Cable

Construction

Central strength member	ø2.5 mm FRP rod									
Fibre colour code	1	Red	7	Brown						
	2	Green	8	Violet						
	3	Blue	9	Turquoise						
	4	Yellow	10	Black						
	5	White	11	Orange						
	6	Grey	12	Pink						
Loose tube	ø2.3 mm gel-filled loose tubes, with 2 – 12 fibres each, up to 24 tubes in two layers, for lay-up refer to B04									
Water blocking	The core is water blocked using swelling tape and tread									
Wrapping	Polyester nonwoven									
Ripcord	Polyester ripcord for easy slitting of the sheath									
Sheath	1.5 mm blue (black optional) FireBur®, halogen free. Flame resistant thermoplastic sheathing compound according to EN 50290-2-27, UV stabilized									
Print legend	Draka UC ^{FIBRE} I/O ST LSHF 1.8 kN <Number of Elements> x <Fibre count per element> <Fibre type> <Fibre brand> <Item No> <Factory No> <Batch Number> <Meter mark> U-DQH <Number of Elements> x <Fibre count per element> <Fibre family> <Mode field diameter> /125 <Transmission Class>									

Physical Properties

Attribute	IEC 60794-1-21/22 Method	Limits									
Fibre count	-	48	72	96	120	144	168	216	264	288	
Nominal diameter [mm]	-	10.5	10.5	12.0	13.5	15.0	16.5	15.0	16.5	18.5	
Nominal weight [kg/km]	-	88	90	125	155	190	230	180	225	255	
Short term tensile strength (some days) [N]	E1	1800									
Permanent tensile strength [N]	E1	1200									
Crush (compressive strength) [N/100 mm]	E3	3000									
Impact [J]	E4	20									
Torsion	E7	5 cycles ± 1 turn									
Kink	E10	The cables do not form a kink when a loop is drawn together to a diameter 12 times the cable nominal diameter									
Minimum bending radius [mm]	E11	160	160	180	200	225	250	225	250	280	
Temperature range	F1	Installation		-40 °C to 70 °C							
		Operation *)		-40 °C to 70 °C							
		Storage		-40 °C to 70 °C							
Water penetration	F5	No water on free end									
Heat of combustion [MJ/km]	-		1900	2600	3400	4300	5400	4000	5000		
[kWh/m]			0.53	0.72	0.94	1.19	1.50	1.11	1.39		

*) The cables will operate without any attenuation variation (≤0.05 dB) in the temperature interval -30°C to +60°C. The cables will operate with a maximum attenuation variation of 0.1dB/km in the temperature interval -40°C to +70°C.

N01a: UC^{FIBRE}™ Universal Stranded Loose Tube Cable

Product Codes

Product Code	Product Description	Fibre Count	Fibre Type	Fibre Data Sheet
	UC ^{FIBRE} I/O ST LSHF 1.8 kN 4x12 OM3B	48	MaxCap-BB-OM3	C31
	UC ^{FIBRE} I/O ST LSHF 1.8 kN 6x12 OM3B	72	MaxCap-BB-OM3	C31
	UC ^{FIBRE} I/O ST LSHF 1.8 kN 8x12 OM3B	96	MaxCap-BB-OM3	C31
	UC ^{FIBRE} I/O ST LSHF 1.8 kN 12x12 OM3B	144	MaxCap-BB-OM3	C31
60019790	UC ^{FIBRE} I/O ST LSHF 1.8 kN 4x12 OM4B	48	MaxCap-BB-OM4	C32
	UC ^{FIBRE} I/O ST LSHF 1.8 kN 6x12 OM4B	72	MaxCap-BB-OM4	C32
	UC ^{FIBRE} I/O ST LSHF 1.8 kN 8x12 OM4B	96	MaxCap-BB-OM4	C32
	UC ^{FIBRE} I/O ST LSHF 1.8 kN 12x12 OM4B	144	MaxCap-BB-OM4	C32
	UC ^{FIBRE} I/O ST LSHF 1.8 kN 2x12 OM5	24	WideCap-OM5	C39
	UC ^{FIBRE} I/O ST LSHF 1.8 kN 4x12 OM5	48	WideCap-OM5	C39
	UC ^{FIBRE} I/O ST LSHF 1.8 kN 6x12 OM5	72	WideCap-OM5	C39
	UC ^{FIBRE} I/O ST LSHF 1.8 kN 8x12 OM5	96	WideCap-OM5	C39
60037500	UC ^{FIBRE} I/O ST LSHF 1.8 kN 1x12 SM2D	12	OS2 G.652.D	C06e
60019392	UC ^{FIBRE} I/O ST LSHF 1.8 kN 2x12 SM2D	24	OS2 G.652.D	C06e
60037503	UC ^{FIBRE} I/O ST LSHF 1.8 kN 4x6 SM2D	24	OS2 G.652.D	C06e
60026285	UC ^{FIBRE} I/O ST LSHF 1.8 kN 4x12 SM2D	48	OS2 G.652.D	C06e
60037520	UC ^{FIBRE} I/O ST LSHF 1.8 kN 6x12 SM2D	72	OS2 G.652.D	C06e
60019394	UC ^{FIBRE} I/O ST LSHF 1.8 kN 8x12 SM2D	96	OS2 G.652.D	C06e
60045388	UC ^{FIBRE} I/O ST LSHF 1.8 kN 11x12 SM2D	132	OS2 G.652.D	C06e
60020128	UC ^{FIBRE} I/O ST LSHF 1.8 kN 12x12 SM2D	144	OS2 G.652.D	C06e
60049567	UC ^{FIBRE} I/O ST LSHF 1.8 kN 4x12 SM2D BK	48	OS2 G.652.D	C06e
60048463	UC ^{FIBRE} I/O ST LSHF 1.8 kN 8x12 SM2D BK	96	OS2 G.652.D	C06e
60020239	UC ^{FIBRE} I/O ST LSHF 1.8 kN 12x12 SM2D BK	144	OS2 G.652.D	C06e
60046154	UC ^{FIBRE} I/O ST LSHF 1.8 kN 4x12 SM7A1	48	OS2 BendBright G.657.A1	C17
	UC ^{FIBRE} I/O ST LSHF 1.8 kN 6x12 SM7A1	72	OS2 BendBright G.657.A1	C17
	UC ^{FIBRE} I/O ST LSHF 1.8 kN 8x12 SM7A1	96	OS2 BendBright G.657.A1	C17
	UC ^{FIBRE} I/O ST LSHF 1.8 kN 12x12 SM7A1	144	OS2 BendBright G.657.A1	C17

© PRYSMIAN GROUP 2017, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.