

760201152 | 360-iP-1100-E-1U-BLANK

**SYSTIMAX 360™ iPatch® 1100 Evolve Panel, 24 port without modules**



## Product Classification

Portfolio	SYSTIMAX®
Brand	iPatch®   SYSTIMAX 360™
Product Type	Copper patch panel
Regional Availability	Asia   Australia/New Zealand   EMEA   Latin America   North America

## Dimensions

Depth	206.50 mm   8.13 in
Diameter Over Dielectric, maximum	1.168 mm   0.046 in
Height	44.45 mm   1.75 in
Width	482.60 mm   19.00 in

## Electrical Specifications

Current Rating	1.5 A @ 20 °C 1.5 A @ 68 °F
Dielectric Withstand Voltage, RMS, conductive surface	1500 Vac @ 60 Hz
Insulation Resistance, minimum	500 MOhm

## Environmental Specifications

Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Safety Standard	cUL   UL
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)

## General Specifications

Intelligence Type	iPatch® enabled
Total Ports, quantity	24
Cable Type	U/UTP (unshielded)
Color	Silver
Package Quantity	1
Rack Units	1

## Mechanical Specifications

Plug Insertion Life, minimum	750 times
Wiring	T568A   T568B

## Regulatory Compliance/Certifications

Agency	Classification
--------	----------------

# Product Specifications



760201152 | 360-iP-1100-E-1U-BLANK

RoHS 2011/65/EU  
ISO 9001:2008