

760109512 | 360G2 Cartridge 6-SC-LS-AQ-Pigtails A
SYSTIMAX 360G2 Cartridge 6 SC LazrSPEED® Aqua with Pigtails A



Construction Materials

Fiber Type	LazrSPEED® 550, 50 µm multimode fiber (OM4)
Total Fibers, quantity	6

Dimensions

Depth	119.38 mm 4.70 in
Height	30.48 mm 1.20 in
Pigtail Length	1.5 m 4.9 ft
Width	91.44 mm 3.60 in

Environmental Specifications

Safety Standard	UL
-----------------	----

General Specifications

Brand	SYSTIMAX 360™ SYSTIMAX®
Product Type	Cartridge
Interface, front	SC
Adapter Color	Aqua
Interface Feature, front	Standard
Package Quantity	1
Total Ports, quantity, front	6

Optical Performance

Insertion Loss Change, mating	0.30 dB
Insertion Loss Change, temperature	0.30 dB
Insertion Loss, typical	0.40 dB
Return Loss, minimum	20.0 dB

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system



Included Products

860278738 (Product Component—not orderable) — LazrSPEED® 550 SC 0.9 mm Pigtail, blue, 1.5 m

- 760044859 | X-TB-5K-BL-F/G (Product Component—not orderable) — LazrSPEED® 900µm Tight Buffered Fiber
- 460125834 (Product Component—not orderable) — Behind The Wall Pre-Radiused SC Connector for 0.9 mm Fiber, multimode

860278746 (Product Component—not orderable) — LazrSPEED® 550 SC 0.9 mm Pigtail, orange, 1.5 m

- 760044867 | X-TB-5K-OR-F/G (Product Component—not orderable) — LazrSPEED® 900µm Tight Buffered Fiber
- 460125834 (Product Component—not orderable) — Behind The Wall Pre-Radiused SC Connector for 0.9 mm Fiber, multimode

860278753 (Product Component—not orderable) — LazrSPEED® 550 SC 0.9 mm Pigtail, green, 1.5 m

- 760044875 | X-TB-5K-GR-F/G (Product Component—not orderable) — LazrSPEED® 900µm Tight Buffered Fiber
- 460125834 (Product Component—not orderable) — Behind The Wall Pre-Radiused SC Connector for 0.9 mm Fiber, multimode

860278761 (Product Component—not orderable) — LazrSPEED® 550 SC 0.9 mm Pigtail, brown, 1.5 m

- 760044883 | X-TB-5K-BR-F/G (Product Component—not orderable) — LazrSPEED® 900µm Tight Buffered Fiber
- 460125834 (Product Component—not orderable) — Behind The Wall Pre-Radiused SC Connector for 0.9 mm Fiber, multimode

860278779 (Product Component—not orderable) — LazrSPEED® 550 SC 0.9 mm Pigtail, slate, 1.5 m

- 760044891 | X-TB-5K-SL-F/G (Product Component—not orderable) — LazrSPEED® 900µm Tight Buffered Fiber
- 460125834 (Product Component—not orderable) — Behind The Wall Pre-Radiused SC Connector for 0.9 mm Fiber, multimode

860278787 (Product Component—not orderable) — LazrSPEED® 550 SC 0.9 mm Pigtail, white, 1.5 m

- 760044909 | X-TB-5K-WH-F/G (Product Component—not orderable) — LazrSPEED® 900µm Tight Buffered Fiber
- 460125834 (Product Component—not orderable) — Behind The Wall Pre-Radiused SC Connector for 0.9 mm Fiber, multimode

700207012 | MFA-SC06-AQ-SHUTTERED — LazrSPEED® SC Multiport Shuttered Adapter, Aqua, Single Pack

* Footnotes

Insertion Loss Change, mating Maximum insertion loss change after 500 matings

Insertion Loss Change, temperature Maximum insertion loss change from -10 °C to +60 °C (+14 °F to +140 °F)