

760109553 | 360G2 Cartridge 6-SC-SM-BL-Pigtails A  
**SYSTIMAX 360G2 Cartridge 6 SC TeraSPEED® Blue with Pigtails A**



## Construction Materials

Fiber Type	TeraSPEED®, zero water peak singlemode fiber (G.652.D, G.657.A1 or G.652.D, G.657.A1   OS2)
Total Fibers, quantity	6

## Dimensions

Depth	119.38 mm   4.70 in
Height	30.48 mm   1.20 in
Pigtail Length	1.5 m   4.9 ft
Width	91.44 mm   3.60 in

## Environmental Specifications

Safety Standard	UL
-----------------	----

## General Specifications

Brand	SYSTIMAX 360™   SYSTIMAX®
Product Type	Cartridge
Interface, front	SC
Adapter Color	Blue
Interface Feature, front	Standard
Package Quantity	1
Total Ports, quantity, front	6

## Optical Performance

Insertion Loss Change, mating	0.30 dB
Insertion Loss Change, temperature	0.30 dB
Insertion Loss, typical	0.40 dB
Return Loss, minimum	55.0 dB

## Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system



## Included Products

---

- 860240670 (Product Component—not orderable) — TeraSPEED® SC 0.9 mm Pigtail, blue, 1.5 m
- 760095596 | X-TB-8W-BL-F/G (Product Component—not orderable) — TeraSPEED® 900µm Tight Buffered Fiber
  - 460125842 (Product Component—not orderable) — Behind The Wall Pre-Radiused SC Connector for 0.9 mm Fiber, single-mode
  - 760211201 | X-TB-8G-BL-F/G (Product Component—not orderable) — 900µm Tight Buffered Fiber
- 860240688 (Product Component—not orderable) — TeraSPEED® SC 0.9 mm Pigtail, orange, 1.5 m
- 760095604 | X-TB-8W-OR-F/G (Product Component—not orderable) — TeraSPEED® 900µm Tight Buffered Fiber
  - 460125842 (Product Component—not orderable) — Behind The Wall Pre-Radiused SC Connector for 0.9 mm Fiber, single-mode
  - 760211219 | X-TB-8G-OR-F/G (Product Component—not orderable) — 900µm Tight Buffered Fiber
- 860240696 (Product Component—not orderable) — TeraSPEED® SC 0.9 mm Pigtail, green, 1.5 m
- 760095612 | X-TB-8W-GR-F/G (Product Component—not orderable) — TeraSPEED® 900µm Tight Buffered Fiber
  - 460125842 (Product Component—not orderable) — Behind The Wall Pre-Radiused SC Connector for 0.9 mm Fiber, single-mode
- 860240704 (Product Component—not orderable) — TeraSPEED® SC 0.9 mm Pigtail, brown, 1.5 m
- 760095620 | X-TB-8W-BR-F/G (Product Component—not orderable) — TeraSPEED® 900µm Tight Buffered Fiber
  - 460125842 (Product Component—not orderable) — Behind The Wall Pre-Radiused SC Connector for 0.9 mm Fiber, single-mode
- 860240712 (Product Component—not orderable) — TeraSPEED® SC 0.9 mm Pigtail, slate, 1.5 m
- 760095638 | X-TB-8W-SL-F/G (Product Component—not orderable) — TeraSPEED® 900µm Tight Buffered Fiber
  - 460125842 (Product Component—not orderable) — Behind The Wall Pre-Radiused SC Connector for 0.9 mm Fiber, single-mode
- 860240720 (Product Component—not orderable) — TeraSPEED® SC 0.9 mm Pigtail, white, 1.5 m
- 760095646 | X-TB-8W-WH-F/G (Product Component—not orderable) — TeraSPEED® 900µm Tight Buffered Fiber
  - 460125842 (Product Component—not orderable) — Behind The Wall Pre-Radiused SC Connector for 0.9 mm Fiber, single-mode
- 760049783 | SFA-SC06-BL-SHUTTERED — TeraSPEED® SC Multiport Shuttered Adapter, Blue, Single Pack

## \* Footnotes

---

Insertion Loss Change, mating      Maximum insertion loss change after 500 matings

Insertion Loss Change, temperature      Maximum insertion loss change from -10 °C to +60 °C (+14 °F to +140 °F)