

LANmark-OF Splice Cassettes

LANmark-OF Splice Cassette Heat Shrink Protectors

Nexans ref.: [N890.090](#)

- Splice cassette for management of splices
- Heat Shrink protectors
- Large splice cassette

DESCRIPTION

Family of patch panel accessories for termination of cable when using fusion splicing techniques.

The cassette protects the fusion splices and holds them in position.

The splice cassettes with heatshrink protectors can be used for both 250 and 900 μm coated fibres. Hence these cassettes are compatible with LANmark-OF Tight Buffer, Loose Tube and Micro-Bundle cables. Splicing with heat shrink protectors can also be used for both LANmark-OF Maxistrip and Tight Buffer Pigtails.


The cassettes have 12 splice positions. When using LANmark-OF Maxistrip Pigtails 2 protectors can be stacked on top of each other increasing capacity to 24 splices per cassette.

The Nexans fibre panels can hold up to 4 splice cassettes and only the top splice cassette needs a cover.

The large splice cassettes (N890.090, N890.091 and N890.092) can be installed in the LANmark-OF patch panels (N439.*) and LANsense-OF sliding preloaded patch panels (N883.2B*).

The splice cassettes are fixed to each other at the back of the cassettes with the provided hinges. This feature facilitates the inspection after installation since the cassettes can be lifted and tilted.

The cassette facilitates 2 rings of routing: an inner ring for the fibres of the pigtails and an outer ring for the fibres of the cable.



LANmark-OF

STANDARDS

International ISO/IEC 11801