

760237046 | CPP-SDDM-SL-1U-24

Discrete Distribution Module Panel, SL, STP, 1U, 24 port



Product Classification

Portfolio	CommScope®
Product Type	Copper patch panel
Regional Availability	Asia Australia/New Zealand EMEA Latin America North America

Dimensions

Depth, with cable management	4.70 in
Diameter Over Dielectric, maximum	1.168 mm 0.046 in
Diameter Over Dielectric, minimum	0.762 mm 0.030 in
Height	44.45 mm 1.75 in
Width	482.60 mm 19.00 in

Electrical Specifications

ANSI/TIA Category	6 6A
-------------------	--------

Environmental Specifications

Flammability Rating	UL 94 V-0
Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Safety Standard	cUL UL
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)

General Specifications

Total Ports, quantity	24
Cable Type	S/STP (shielded)
Brand	CommScope®
Color	Black
Modules, quantity	0
Package Quantity	1
Rack Type	EIA 19 in
Rack Units	1

Mechanical Specifications

Panel Style	Straight
Material Type	High-impact, flame retardant, thermoplastic Powder-coated steel

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant

Product Specifications

760237046 | CPP-SDDM-SL-1U-24

ISO 9001:2008 Designed, manufactured and/or distributed under this quality management system

