

FBXLCUC11

LazrSPEED® 550 LC to Unconnectorized, Fiber Pigtail, 0.9 mm Riser - SBJ

Ordering Details

Part Number	Jacket Color	Breakout Length	Cable Glands	Pulling Grips, qty	Length
FBXLCUC11-MXF005	Aqua	N/A	No glands	0	5 ft

LazrSPEED® 550 LC to Unconnectorized, Fiber Pigtail, 0.9 mm Riser - SBJ, aqua jacket, 5 ft

Product Classification

Portfolio	CommScope®
Brand	LazrSPEED®
Product Type	Fiber pigtail, simplex
Regional Availability	Asia Australia/New Zealand EMEA Latin America North America

Construction Materials

Fiber Type	OM4, LazrSPEED® 550
Total Fibers, quantity	1

Dimensions

Cord Length, maximum	23 ft 7 m
Cord Length, minimum	2 ft 1 m
Ordering Note	For lengths greater than 999 ft (304 m), orders must be in meters Minimum length may vary based on cable configuration

Environmental Specifications

Environmental Space	Low Smoke Zero Halogen (LSZH) Riser
Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)

General Specifications

Construction Type	Pigtail, jacketed
Interface, connector A	LC
Interface Feature, connector A	Standard
Color, connector A	Beige
Interface, connector B	Unterminated

Mechanical Specifications

Cable Retention Strength, maximum	2.00 lb @ 90 ° 5.00 lb @ 0 °
-----------------------------------	---------------------------------

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system

FBXLCUC11



Included Products

N-001-RF-5K-F09 (Product Component—not orderable) — LazrSPEED® 0.9mm Low Smoke Zero Halogen Reinforced Buffered Fiber Cable

- CS-5K-TB (Product Component—not orderable) — LazrSPEED® 550 OM4 Bend-Insensitive Multimode Fiber

460125271 (Product Component—not orderable) — Behind The Wall Pre-Radiused LC Connector for 0.9 mm Fiber, multimode