



20A model :
H6UK90-20A_OE/3B-1



20 Amp
Open end

Input Rating : 20A, 230V
Inlet : 20A open end
Cordset : 3 meter 2.5mm sq. H05V V-F cordset
Protection : NIL
Circuit Details : Output 20A max. U K # 1 - 6

13A model :
H6UK90-13A_BS/3B-1



13 Amp
BS1363

Input Rating : 13A, 230V
Inlet : 13A BS1363 plug
Cordset : 3 meter 1.5mm sq. H05V V-F cordset
Protection : NIL
Circuit Details : Output 13A max. U K # 1 - 6

16A model :
H6UK90-16A_EN/3B-1



IEC 60309
16A 2P+E PLUG

Input Rating : 16A, 230V
Inlet : 16A IEC60309 2P+E plug
Cordset : 3 meter 1.5mm sq. H05V V-F cordset
Protection : NIL
Circuit Details : Output 16A max. U K # 1 - 6

10A model :
H6UK90-10A_C14/3B-1



10 Amp
IEC320 C14

Input Rating : 10A, 230V
Inlet : 10A IEC320 C14 plug
Cordset : 3 meter 1.5mm sq. H05V V-F cordset
Protection : NIL
Circuit Details : Output 10A max. U K # 1 - 6

16A model :
H6UK90-16A_C20/3B-1



16 Amp
IEC320 C20

Input Rating : 16A, 230V
Inlet : 16A IEC320 C20 plug
Cordset : 3 meter 1.5mm sq. H05V V-F cordset
Protection : NIL
Circuit Details : Output 16A max. U K # 1 - 6

Single phase basic PDU

Outlet : 13A Rated BS1363 UK x 6

AUSTIN HUGHES
Design. Manufacturing. Global Services.

The company reserves the right to modify product specifications without prior notice and assumes no responsibility for any error which may appear in this publication.

Copyright 2016 Austin Hughes Electronics Ltd. All rights reserved.

EMC Compliance : FCC & CE certified
Safety Compliance : CE / LVD certified
Environment Compliance : RoHS2 & REACH

Operating Temperature : -5 to 60 °C
Storage Temperature : -25 to 65 °C
Operating Altitude : 0 to 2,000 m
Storage Altitude : 0 to 15,000 m
Humidity : 8 to 95% RH, non-condensing

Dimension : 437.5 (W) x 65 (D) x 55 (H) mm
Material : Extrusion
Color : Black