


| 20A model : | Fuse | MCB |
|-----------------------|------|-----|
| H6UK90-20A-F_OE/3B-1 | 1 | - |
| H6UK90-20A-CR_OE/3B-1 | - | 1 |



Input Rating : 20A, 230V
Inlet : 20A open end
Cordset : 3 meter 2.5mm sq. H05V V-F cordset
Protection : 20A resettable fuse or
20A hydraulic MCB x 1
Circuit Details : Output 20A max. U K #1 - 6

| 13A model : | Fuse | MCB |
|-----------------------|------|-----|
| H6UK90-13A_BS/3B-1 | - | - |
| H6UK90-13A-CR_BS/3B-1 | - | 1 |



Input Rating : 13A, 230V
Inlet : 13A BS1363 plug
Cordset : 3 meter 1.5mm sq. H05V V-F cordset
Protection : 13A glass fuse in BS1363 plug or
13A hydraulic MCB x 1
Circuit Details : Output 13A max. U K #1 - 6

| 16A model : | Fuse | MCB |
|-----------------------|------|-----|
| H6UK90-16A-F_EN/3B-1 | 1 | - |
| H6UK90-16A-CR_EN/3B-1 | - | 1 |



Input Rating : 16A, 230V
Inlet : 16A IEC60309 2P+E plug
Cordset : 3 meter 1.5mm sq. H05V V-F cordset
Protection : 16A resettable fuse or
16A hydraulic MCB x 1
Circuit Details : Output 16A max. U K #1 - 6

| 10A model : | Fuse | MCB |
|------------------------|------|-----|
| H6UK90-10A-F_C14/3B-1 | 1 | - |
| H6UK90-10A-CR_C14/3B-1 | - | 1 |



Input Rating : 10A, 230V
Inlet : 10A IEC320 C14 plug
Cordset : 3 meter 1.5mm sq. H05V V-F cordset
Protection : 10A resettable fuse or
10A hydraulic MCB x 1
Circuit Details : Output 10A max. U K #1 - 6

| 16A model : | Fuse | MCB |
|------------------------|------|-----|
| H6UK90-16A-F_C20/3B-1 | 1 | - |
| H6UK90-16A-CR_C20/3B-1 | - | 1 |



Input Rating : 16A, 230V
Inlet : 16A IEC320 C20 plug
Cordset : 3 meter 1.5mm sq. H05V V-F cordset
Protection : 16A resettable fuse or
16A hydraulic MCB x 1
Circuit Details : Output 16A max. U K #1 - 6

Single phase basic PDU

Outlet : 13A Rated BS1363 UK x 6



The company reserves the right to modify product specifications without prior notice and assumes no responsibility for any error which may appear in this publication.

Copyright 2017 Austin Hughes Electronics Ltd. All rights reserved.

EMC Compliance : FCC & CE certified
Safety Compliance : CE / LVD certified
Environment Compliance : RoHS2 & REACH

Operating Temperature : -5 to 60 °C
Storage Temperature : -25 to 65 °C
Operating Altitude : 0 to 2,000 m
Storage Altitude : 0 to 15,000 m
Humidity : 8 to 95% RH, non-condensing

Dimension : 437.5 (W) x 65 (D) x 55 (H) mm
Material : Extrusion
Color : Black