

TECHNICAL DATA SHEET

CABLE REFERENCE : 8723 PE (V.S) BLK

ISSUE NO. : 1

ISSUE DATE : March 9, 2013

CABLE CONSTRUCTION

Type	8723 PE				
Test Standard	UL1581				
1. Conductor	Material	Stranded Tinned Copper			
	Nom.O.D.(mm)	0.24×7	Up	+0.008	
			Down	-0.008	
2. Insulation	Material	SPE			
	Diameter	1.20(+/-0.13)mm×2×2			
	Colours	(White,Green)/(Red,Black)			
3. Shield	Material	AL-foil			
	Colour	Blue			
4. Drain	Material	Stranded Tinned Copper			
	Nom.O.D.(mm)	0.19×7	Up	+0.008	
			Down	-0.008	
5. Jacket	External O.D.mm	5.90(+/-0.20)			
	Surface	Clean,Smooth			
	Material	SPE			
	Color	Black			
Electrical Characteristics	Item		Standard		
	Conductor Resistance @ 20C		< 6.53 Ω/100M		
	Min.Insulation DC Resistance @ 20C		>200 MΩ*M		
	Rated Volage		300V		
	Rated Temperature		-20°C to +80°C		



Information in this data sheet supplied to users is based on general experience and is given in good faith, but because of the many particular factors which are outside our knowledge which affect the use of the products, no warranty is given nor is to be implied with respect to such information. Users should make their own enquiries to determine the stability of products for any particular use.