


TECHNICAL DATA SHEET

CABLE REFERENCE : CW1308 6PR

ISSUE NO. : 1

ISSUE DATE : 2 MAR, 2012.

CABLE CONSTRUCTION

Category Type	CW1308 6PR				
Test Standard	UL1581				
1. Conductor	Material	Solid Bare Copper			
	Nom.O.D.(mm)	0.4	Up		+0.010
			Down		-0.010
2. Insulation	Material	FR-PVC			
	Diameter	0.90(+/-0.10)x2x6			
Color	white/orange, orange/white, blue/white, white/blue, grey/white, white/grey, green/white, white/green, red/blue, blue/red, brown/white, white/brown				
3. Rip-Cord	Material	Nylon			
	Color	White			
4. Jacket	External O.D.mm	5.70(+/-0.20)			
	Surface	Clean, Smooth			
	Material	LSF-PVC			
	Color	white			
CHARACTERISTICS	Item	Description	Standard		
	1. Cond. Resistance	20°C, Conductor DC Resistance	< 10.54 Ω/100M		
	2. Min. Insulation DC Resistance	20°C, Insulation DC Resistance	>200 MΩ*M		
	3. Rated Volage	300v		
	4. Rated Temperature	80°C		



Information in this data sheet supplied to users is based on general experience and is given in good faith, but because of the many particular factors which are outside our knowledge which affect the use of the products, no warranty is given nor is to be implied with respect to such information. Users should make their own enquiries to determine the stability of products for any particular use.