

Slick Line 8kn Rope Orange (L)4250Mtr



PRODUCT DESCRIPTION

Suitable for pulling cable through standard bore subduct and ducting using commonly used cable pulling techniques and equipment, minimum breaking load of 8kN

MATERIAL TECHNICAL SPECIFICATION

Outer Sheath	HDPE monofilament in 16 plait construction
Outer Sheath Colour	Orange
Rope Core	HT multifilament polyester
Rope Core Colour	White
Bobbin Core Length	510mm
Bobbin Core Diameter	140mm (OD)

PHYSICAL PROPERTIES

	Value	Units	Tolerance	Test Method
Length	4,250	metre	-0/+20	BS5053-5.1
Rope diameter	6.0	mm	+/-1	BS5053
Minimum breaking load	8.0	kN	-	-
Max extension at 60% minimum spliced breaking load	5.5	%	-	BT MA 274A
Mass per unit length	19.0	gm/m	+/-1	-
Mass per bobbin	69.5	kg	+/-5	-
Mass of core	15	kg	+/-1	-
Rotation under load	< 90	Degrees	-	BT MA 274A
Frictional properties	< 390	N	Max.	BT MA 274A
Abrasive properties	< 0.5	mm	Max.	BT MA 274A

APPLICATION

Cable / duct pulling.