

Network Infrastructure and cable labelling printer kit

PT-E550WNIVP

brother.co.uk/PT-E550WNIVP



Features designed to streamline your identification requirements

LinkWare Live
INTEGRATION

Using the Brother
iLink&Label app

1
Built-in Wi-Fi to connect wirelessly to your smartphone and print labels using free apps

2
Prints labels from 3.5mm to 24mm wide

3
Advanced label cutter with easy-peel function to print labels in a long strip, keeping them in the correct order

4
Easy to read backlit LCD display

5
Dedicated hotkeys to easily create cable, patch panel, equipment and faceplate ID labels: General, faceplate, cable wrap, cable flag, patch panel, punch down block

6
Separate numeric keypad for quick entry of numbers

7
Save frequently used labels to the memory for instant recall and printing when required

8
Upload* company logos or specialist symbols from your PC to include on your labels whenever required. Includes popular industrial symbols

9
Built-in barcode printing function

10
Serialise function to print multiple labels automatically in the correct numbered sequence

11
Upload* cable ID's from your PC using P-touch Editor or from your smartphone using iLink&Label or Mobile Transfer Express apps. Then select the range of cable ID's to print labels while on-site.

12
USB port to print labels or upload* content from your PC using P-touch Editor



* Upload function not available on macOS

Features and specifications

PT-E550WNIVP

Printer features

Display type	16 characters x 3-line backlit graphic LCD with print preview
Interfaces	USB, Wi-Fi and Wireless Direct
Print speed	30mm/second (powered by AC adapter) 20mm/second (powered by battery)
Maximum tape width	24mm
Maximum print height	18mm
Cutter type	Automatic (full and half cut)
Powered by	BA-E001 Li-ion rechargeable battery (supplied) 6 x AA alkaline/rechargeable batteries (LR6/HR6 - not supplied)

Label creation

Dedicated labelling functions	General Faceplate Patch panel Punch-down block Cable wrap Cable flag Heat shrink tube Serialise (automatic number incrementation)
Fonts	14 fonts 10 styles 6 to 48 point size
Maximum lines per label	7 (using 24mm label width)
Maximum text blocks	99
Symbols	384
Frames	7
Automatic numbering	01-99
Number of copies	01-99
Vertical text printing	Yes
Rotated text (for cable labelling)	Rotate once Rotate and repeat

PC software main features

Supported operating systems	Windows® 10 / 8.1 / Server 2019 / Server 2016 / Server 2012 R2 / Server 2012 MacOS 10.12.x - 10.15.x Mac OS X 10.7.x - 10.11.x
Cable labelling wizard	Yes (Windows only)
Fonts	All installed TrueType fonts
Font styles	12
Image support	JPG, BMP, TIFF, PNG
Frames	153
Barcodes	21 protocols including 1D/2D barcodes

Memory

Maximum characters per label	1,500
Label memory locations	99

Mobile applications

iOS and Android	iLink&Label to print cable ID's from Fluke Networks Linkware Live Mobile Cable Label Tool Mobile Transfer Express
-----------------	--

Supplies

Tape cassettes	Brother TZe tape cassettes (3.5mm - 24mm) Brother HSe heat shrink tube (5.8mm - 23.6mm)
----------------	--

Weights and dimensions

Printer dimensions: 126mm (w) x 250mm (h) x 94mm (d)
Printer weight: 1.05kg

Included items:

- PT-E550W label printer
- Rechargeable Li-ion battery
- AC adapter
- 24mm black on white self-laminating tape cassette for cable identification
- 9mm black on white strong adhesive tape cassette for patch panel and equipment identification
- USB cable
- Documentation
- Carry case



brother

at your side

Contact:

www.brother.co.uk

Brother UK Ltd

Shepley Street, Audenshaw,
Manchester M34 5JD
Tel: +44(0)333 777 4444