

## Essential-6 Outlet Modules

Essential-6 LJ6C outlet module 25x39.5mm

Nexans ref.: [N424.623](#)

- Complies to the latest Category 6 standards
- 25x39.5mm dimensions
- Unshielded
- LSA+ termination
- UK white
- Fits LJ6C structural hardware

### Description

#### Application

The Nexans Essential-6 unshielded outlet modules are manufactured and tested to the latest Category 6 specifications. They support Class E applications up to 250 MHz. When installed in conjunction with Essential-6 cable and patch panels, a 25 year Class E Link Certificate can be obtained from the Nexans web site.

#### Design

The Essential-6 outlet modules are compatible with the complete Essential-6 range and are designed to fit into all LJ6C format floorplates or structural hardware. (please check compatibility). They can be used with all types of UTP Category 6 cable with solid wire from 22 to 24 AWG. The spring shuttered modules come in gloss white finish, matching with most British style structural hardware. They are also available in a 25x50mm format (even with a low profile design for the use in shallow backboxes or floorboxes) and in a triple port version with 50x50mm dimensions.

The modules are equipped with transparent label holders fitted with a blank paper label for customised port identification.

#### Performance

The Essential-6 outlet modules are compliant with the specifications of ISO/IEC 11801: 2002.

#### Installation

- Fast and easy termination by LSA+ punch-down tooling.
- Wiring according to colour code T568B.
- Centrally positioned tie wrap bridges ensure cable strain relief.
- Supplied with tie wraps.
- Labelling windows included.
- Fits most LJ6C structural hardware (check acceptance).
- Max. depth from rear of face plate or floorbox plate: 26mm.



**essential-6**

#### Standards

**International ISO/IEC 11801**

## Essential-6 Outlet Modules

Essential-6 LJ6C outlet module 25x39.5mm

Nexans ref.: [N424.623](#)

### Characteristics

Construction characteristics	
Connector type	RJ45 and LSA+ IDC
Screen	Unshielded
Dimensional characteristics	
Width	25 mm
Depth	32 mm
Height	39.5 mm
Usage characteristics	
Number of ports	1
Range	essential-6

### Channel Performance

Values given for 2-connector channel, built with Essential-6 cable, outlet and patch panel. (Values specified at 20°C)

Frequency MHz	Insertion Loss dB/100m	NEXT PP dB	PS NEXT dB	ACR dB/100m	PS ACR dB/100m	ELFEXT dB/100m	PSELFEXT dB/100m	Return Loss dB
1	4.0	65.0	62.0	65.0	62.0	63.3	60.3	19.0
4	4.2	63.0	60.5	58.9	56.4	51.2	48.2	19.0
10	6.6	56.6	54.0	50.0	47.4	43.3	40.3	19.0
16	8.3	53.2	50.6	44.9	42.3	39.2	36.2	18.0
20	9.3	51.6	49.0	42.3	39.7	37.2	34.2	17.5
31.25	11.7	48.4	45.7	36.7	34.0	33.4	30.4	16.5
62.5	16.9	43.4	40.6	26.5	23.7	27.3	24.3	14.0
100	21.7	39.9	37.1	18.2	15.4	23.3	20.3	12.0
155	27.6	36.7	33.8	9.1	6.2	19.5	16.5	10.1
200	31.7	34.8	31.9	3.1	0.1	17.2	14.2	9.0
250	35.9	33.1	30.2	-2.8	-5.8	15.3	12.3	8.0