

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

TECHLUBE PHD POURABLE CABLE LUBRICANT

Safety Data Sheet dated 28/1/2021, version 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: TECHLUBE PHD POURABLE CABLE LUBRICANT
SDS code: P10699
UFI: XVUT-3TGN-HY09-5FKJ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Lubricant
Industrial uses

Uses advised against:

No uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Manufacturers:

Socomore SASU
Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France
Tel : +33 (0)2 97 43 76 83 - Fax : +33 (0)2 97 54 50 26
Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 /
Fax +353 21 4889923 / ireland@socomore.com

Distributors:

SOCOMORE SASU
Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France
Tel : +33 (0)2 97 43 76 83 - Fax : +33 (0)2 97 54 50 26
Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 /
Fax +353 21 4889923 / ireland@socomore.com
Socomore GmbH - c/o MAZARS GmbH - Theodor-Stern-Kai 1 - 60596 Frankfurt am Main -
Deutschland - Tel: +49 (0)89 20 70 28 83 - Fax: +49 (0) 89 88 91 98 16
Socomore Iberia - Calle Diputació, 260 - 08007 Barcelona - Espana - Tel: +34 917 693 962 -
Fax: +34 902 908 966
SOCOMORE SPzoo - Ul. Piekna 18, 00-549 Warszawa Polska - Tel : +48 608 454 114 - Fax
: +48 (22) 621 61 09

Competent person responsible for the safety data sheet:

techdirsocomore@socomore.com

1.4. Emergency telephone number

France : ORFILA (INRS) +33 (0)1 45 42 59
International : CHEMTEL +1-813-248-0585.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Hazard pictograms:

None

Hazard statements:

None

Precautionary statements:

None

Special Provisions:

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

TECHLUBE PHD POURABLE CABLE LUBRICANT

EUH210 Safety data sheet available on request.

Contains

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one: May produce an allergic reaction.
 reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one
 (3:1): May produce an allergic reaction.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards














SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
< 0.1%	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	Index number: 613-088-00-6 CAS: 2634-33-5 EC: 220-120-9	 3.2/2 Skin Irrit. 2 H315  3.3/1 Eye Dam. 1 H318  3.4.2/1 Skin Sens. 1 H317  4.1/A1 Aquatic Acute 1 H400 M=10.  3.1/4/Oral Acute Tox. 4 H302
< 0.1%	reaction mass of 5-chloro-2-methyl-2H-i sothiazol-3-one and 2-methyl-2H-isothiazol- 3-one (3:1)	Index number: 613-167-00-5 CAS: 55965-84-9 REACH No.: 01-21207646 91-48	 3.1/2/Inhal Acute Tox. 2 H330  3.1/2/Dermal Acute Tox. 2 H310  3.1/3/Oral Acute Tox. 3 H301  3.2/1C Skin Corr. 1C H314  3.3/1 Eye Dam. 1 H318  3.4.2/1A Skin Sens. 1A H317  4.1/A1 Aquatic Acute 1 H400 M=100.  4.1/C1 Aquatic Chronic 1 H410 M=100. EUH071

Contains Propane-1,2-diol ($\geq 0.3\%$ - $< 0.5\%$) CAS: 57-55-6: substance with a UK workplace exposure limit

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not induce vomiting. Obtain a medical examination.

In case of Inhalation:

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

TECHLUBE PHD POURABLE CABLE LUBRICANT

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

Treatment:

No particular treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Do not eat or drink while working.

7.2. Conditions for safe storage, including any incompatibilities

Product should be stored at above freezing conditions.(>0°C)

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

None in particular

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

TECHLUBE PHD POURABLE CABLE LUBRICANT

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

Propane-1,2-diol - CAS: 57-55-6

- OEL Type: National - TWA(8h): 10 mg/m³ - Notes: UK - Propane-1,2-diol particulates

- OEL Type: National - TWA(8h): 474 mg/m³, 150 ppm - Notes: UK - Propane-1,2-diol total vapour and particulates

DNEL Exposure Limit Values

N.A.

PNEC Exposure Limit Values

N.A.

Biological Exposure Index

N.A.

8.2. Exposure controls

See below, example of PPE to use.

Eye protection:

Safety goggles (EN 166)

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

NR (natural rubber, natural latex).

NBR (nitrile rubber).

PVA (Polyvinyl alcohol).

PVC (polyvinyl chloride).

Butyl rubber (isobutylene-isoprene copolymer)

Respiratory protection:

Not needed for normal use.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

Other conditions affecting workers exposure:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Appearance and colour:	VISCOUS LIQUID	--	--
Odour:	N.A.	--	--
Odour threshold:	N.A.	--	--
pH:	7	--	--
Melting point / freezing point:	<0°C	--	--
Initial boiling point and boiling range:	100 °C	--	--
Flash point (°C):	N.A.	--	--
Flash Point (°F):	N.A.	--	--

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
TECHLUBE PHD POURABLE CABLE LUBRICANT

Evaporation rate:	N.A.	--	--
Solid/gas flammability:	N.A.	--	liquid
Upper/lower flammability or explosive limits:	N.A.	--	--
Vapour pressure:	N.A.	--	--
Vapour density:	N.A.	--	--
Relative density:	N.A.	--	--
Solubility in water:	N.A.	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient (n-octanol/water):	N.A.	--	--
Auto-ignition temperature:	Not Relevant	--	--
Decomposition temperature:	N.A.	--	--
Viscosity:	2000-3500 cPs (25°C)	ISO 2555	--
Explosive properties:	N.A.	--	--
Oxidizing properties:	N.A.	--	--

9.2. Other information

Properties	Value	Method:	Notes
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--

Volatile Organic compounds - VOCs = 0 %
 Volatile Organic compounds - VOCs = 0 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2001 mg/kg

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

TECHLUBE PHD POURABLE CABLE LUBRICANT

Test: LD50 - Route: Oral - Species: Rat < 5000 mg/kg
Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg
Test: LC50 - Route: Inhalation - Species: Rat > 5 mg/l - Duration: 4h

If not specified in other sections, the information required in Regulation (EU)2015/830 listed below must be considered as not relevant.:

Acute toxicity;
Skin corrosion/irritation;
Serious eye damage/irritation;
Respiratory or skin sensitisation;
Germ cell mutagenicity;
Carcinogenicity;
Reproductive toxicity;
STOT-single exposure;
STOT-repeated exposure;
Aspiration hazard.

Other toxicological information:

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one
Skin : corrosive (rabbit)
Eyes : corrosive (rabbit)

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5

a) Aquatic acute toxicity:

Endpoint: EC10 - Species: Algae = 0.04 mg/l - Duration h: 72 - Notes: Selenestrum capricornutum

Endpoint: EC50 - Species: Daphnia = 3.27 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 0.11 mg/l - Duration h: 72 - Notes: Selenestrum capricornutum

Endpoint: LC50 - Species: Fish = 1.6 mg/l - Duration h: 96 - Notes: Rainbow trout

Endpoint: NOEC - Species: Fish = 0.21 mg/l - Notes: Rainbow trout

Endpoint: NOEC - Species: Daphnia = 1.2 mg/l - Duration h: 504 - Notes: 21 jours

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5

Log Kow 0.7

BCF 6.95

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

No harmful effects expected.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

Codes of wastes (Décision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste):

07 06 99 wastes not otherwise specified

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

TECHLUBE PHD POURABLE CABLE LUBRICANT

SECTION 14: Transport information

14.1. UN number

Not classified as dangerous in the meaning of transport regulations.

14.2. UN proper shipping name

N.A.

14.3. Transport hazard class(es)

N.A.

14.4. Packing group

N.A.

14.5. Environmental hazards

ADR-Environmental Pollutant: No

IMDG-Marine pollutant: No

14.6. Special precautions for user

N.A.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) 2015/830

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 40

Restrictions related to the substances contained:

Restriction 57

Listed or in compliance with the following international inventories:

N.A.

Labelling of detergents (EC Regulations 648/2004 and 907/2006):

N.A.

Labelling of biocides (Regulations 1896/2000, 1687/2002, 2032/2003, 1048/2005, 1849/2006, 1451/2007 and Directive 98/8/EC):

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

TECHLUBE PHD POURABLE CABLE LUBRICANT

N.A.

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

1999/13/EC (VOC directive)

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

None

15.2. Chemical safety assessment

No

SECTION 16: Other information

N.A.: Not Applicable or Not Available

Full text of phrases referred to in Section 3:

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H302 Harmful if swallowed.

H330 Fatal if inhaled.

H310 Fatal in contact with skin.

H301 Toxic if swallowed.

H314 Causes severe skin burns and eye damage.

H410 Very toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

Hazard class and hazard category	Code	Description
Acute Tox. 2	3.1/2/Dermal	Acute toxicity (dermal), Category 2
Acute Tox. 2	3.1/2/Inhal	Acute toxicity (inhalation), Category 2
Acute Tox. 3	3.1/3/Oral	Acute toxicity (oral), Category 3
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Skin Corr. 1C	3.2/1C	Skin corrosion, Category 1C
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Skin Sens. 1	3.4.2/1	Skin Sensitisation, Category 1
Skin Sens. 1A	3.4.2/1A	Skin Sensitisation, Category 1A
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

CCNL - Appendix 1

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

TECHLUBE PHD POURABLE CABLE LUBRICANT

Insert further consulted bibliography

Important confidentiality : this document contains confidential information that is proprietary to SOCOMORE. Subject to legal provisions determining otherwise, the distribution, republication or re-transmission of this document, in full or in part, must be limited to clearly identified individuals, either because they use the product, or to provide HSE information. Any communication of this document outside of this framework without our written consent is strictly forbidden. SOCOMORE strongly advises every recipient of this safety data sheet to read it carefully and to consult experts in the field if necessary or appropriate, in order to understand the information it contains, notably the possible dangers associated with this product. The users must ensure the conformity and completeness of this information with regards to their specific use of the product. The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the responsibility of the purchaser/user to ensure that their activities conform with current legislation in force.

The information is considered correct, but it is not exhaustive and it shall be used only as a guide which is based on the current knowledge of the substance or mixture and it is applicable to the safety precautions appropriate for the product.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
STOT SE:	May cause drowsiness or dizziness
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
TECHLUBE PHD POURABLE CABLE LUBRICANT