



APC Rack PDU 9000 Switched, ZeroU, 32A, 230V, (21) C13 & (3) C19

New

APDU9953

Call for More Information 0800 2799254

- Includes: Installation guide, Rack mounting brackets, Safety guide, Serial configuration cable

Output

Overload Protection	Yes
Maximum Total Current Draw	32
Output Connections	(3) IEC 60320 C19 (21) IEC 60320 C13

Input

Nominal Input Voltage	200V, 208V, 230V
Input frequency	50/60 Hz
Input Connections	IEC 60309 32 A 2P + E
Cord Length	3.1meters
Acceptable Input Voltage	220 - 240VAC
Number of Power Cords	1
Load Capacity	7400VA
Maximum Input Current	32A
Maximum Line Current	32A

Physical

Maximum Height	1829MM, 182.9CM
Maximum Width	56MM, 5.6CM
Maximum Depth	46MM, 4.6CM
Net Weight	7.34KG
Shipping weight	9.95KG

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Rack PDU 9000 Switched, ZeroU, 32A, 230V, (21) C13 & (3) C19 | APDU9953 | Downloaded on 03/01/2021 (EST)

Physical	
Shipping Height	2040MM, 204.0CM
Shipping Width	165MM, 16.5CM
Shipping Depth	124MM, 12.4CM
Color	Black
Units per Pallet	48.0

Environmental	
Operating Temperature	-5 - 45 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0 - 15240meters

Conformance	
Approvals	EAC, EN 55022 class A, EN 55024, EN 61000-3-2, EN 61000-3-3, RCM, VDE
Standard warranty	3 years repair or replace

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.