

Microduct - Microloose Tube cables (12 - 432 fibres)

Microcable 12x12SM SP1434

Contact

Telecom Infrastructure
contact.telecominfra@nexans.com

DESCRIPTION


This compact cable is used for Access, Distribution, City Network and FTTx applications. It is designed to be quickly installed by blowing in micro-ducts.

Characteristics & Applications

- High blowing distance due to the excellent friction properties of the outer sheath
- Right balance between flexibility and rigidity
- Easy installation with mid span access possibility
- Central strength member reinforcement
- All dielectric design
- Waterproof structure

Construction

- Jelly filled microloose tubes containing coloured fibres
- Central FRP strength member
- Very Low friction outer sheath



STANDARDS

International EN 187000;
IEC 60794



Admissible traction load max. (Tm)
150 daN



Ambient installation T°C range
0 .. 40 °C



Operating temp.
-30 .. 60 °C



Storage temperature, range
-40 .. 70 °C



Bending factor when laying
20 (xD)

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 02/03/21 www.nexans.co.uk Page 1 / 2

Microduct - Microloose Tube cables (12 - 432 fibres)

Microcable 12x12SM SP1434

Contact

Telecom Infrastructure
contact.telecominfra@nexans.com

CHARACTERISTICS

Construction characteristics

Fiber optic type	SM
Outer sheath	HDPE
Construction type	Multitube
Strength member	FRP
Metal free	Yes

Dimensional characteristics

Number of optical fibres	144
Number of tubes	12
Nominal outer diameter	9.6 mm
Approximate weight	81 kg/km

Mechanical characteristics

Maximum admissible traction load (T _m)	150 daN
Maximum tensile load during service (T _I)	20.0 daN
Crush resistance (IEC 60794-1-E3)	100 N/cm

Usage characteristics

Installation type	Outdoor - Microduct blowable
Ambient installation temperature, range	0 .. 40 °C
Operating temperature, range	-30 .. 60 °C
Storage temperature, range	-40 .. 70 °C
Bending factor when laying	20 (xD)

SELLING INFORMATION

Standard Marking

Nexans - FIBRE OPTIC CABLE - SPxxxx - XX*YY - FB - TN - metric

XX = Fibre Count

YY = Fibre Type

FB = Produced in Frameries, Belgium

TN = Traceability Number