



T2C Copper Closure, unpressurized, gel sealed, in-line, for up to 300 pair splices

- Watertight splice closure for aerial, underground and direct buried splices in the unpressurized copper telecommunication network
- Fast and easy installation and re-entry process with the gel-sealing system
- Robust and reliable under a wide variety of environmental conditions

Product Classification

Regional Availability	EMEA
Product Type	Gel sealed closure
Product Series	T2C

General Specifications

Application	For use with Polyethylene cables
Cable Capacity, maximum	4
Cable Sealing Type	Gel filled
Closure Style	In-line
Color	Black
Splicing Capacity, maximum	300

Dimensions

Height	165.6 mm 6.52 in
Width	159.4 mm 6.276 in
Length	695 mm 27.362 in
Sheet Opening, nominal	450 mm 17.717 in

Environmental Specifications

Environmental Space	Aerial Buried
----------------------------	-----------------

Packaging and Weights

Included	Cleaning tissues Gel sealing tape Measuring tape Mounting hardware O-ring seal Tie wraps
Packaging quantity	1

Packaging Type

Bag | Carton

Regulatory Compliance/Certifications

Agency

Classification

CHINA-ROHS

Below maximum concentration value

REACH-SVHC

Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS

Compliant

