



# CAT6 UTP ASSEMBLED OUTLETS



## Technical Information

### Features:

- ◆ Fully assembled outlets, including faceplate, module(s) and blanks (where necessary)
- ◆ Cat6 compliant performance
- ◆ 568B wiring
- ◆ Top, bottom or rear cable entry
- ◆ 110 or LSA punch down
- ◆ Only 8mm projection behind faceplate
- ◆ Cable strain relief facility
- ◆ Protected labelling facility
- ◆ 25 year Ultima System Warranty

### Materials

Faceplate, Fascia & RJ45 Jack Housing	ABS UL94V-0
RJ45 Jack Contact	Material: Phosphor bronze, nickel plated. Finish: 50 micron gold plated on plug contact area
IDC Contact	Phosphor bronze, tin plated
Shutter	ABS UL94-HB

### Performance

Insertion Force	20N max.
Retention Strength	7.7kg between Jack and Plug
Operating Temperature	-10°C to 60°C
Mating Cycles	750 cycles min.
IDC Wire Range	23-26 AWG stranded or solid wire. Compatible with 110 and LSA punch down tools



### Part Numbers

Item	Description	Module Type	Faceplate Type	Shielding	Ports	Colour
792389	Assembled Outlet Cat6	Flat Front	Bevelled Faceplate	Unshielded	1 Port	White
792390	Assembled Outlet Cat6	Flat Front	Bevelled Faceplate	Unshielded	2 Ports	White
819423	Assembled Outlet Cat6	Flat Front	Bevelled Faceplate	Unshielded	4 Ports	White