

Co-location - enclosures

The newly launched Prism co-location range has been re-designed to accommodate the requirements of multi user requirements. Available in FI and PI format there are a choice of 2 and 4 compartment products and available in multiple footprint sizes. In the continued struggle for real estate within the data centre, the co-location range will provide the maximum utilisation of space.

Co-location

With a choice of four footprints and two compartment options there is a co-location cabinet for every installation. This can be mated with any PI or FI cabinet to provide a solution for any co-location environment and provide additional revenue per square metre. The

product is supplied with secure internal cable trunking to provide total security for each compartment. This trunking can be accessed from either the top or the bottom of each enclosure.



Typical applications

- Server farms
- Multiple Co-location data centres
- Hosting centres

Features list

- Mesh front doors with combination locks with master Key override
- Mesh rear doors with combination locks with master Key override
- 19 inch mounting angles (2 x Rear 2 x front)
- Secure cable ducting accessible in each location for either top or bottom access
- Heavy duty castors fitted as standard
- Earthing kits supplied to each section

Benefits and additional features

- Floor space optimisation
- Baying PI and FI
- Compatibility with the full range of PI accessories
- Multiple working variants available to assist in providing differing levels of security





Solid floor

Enclosed cable ducting

Vertical mounting profiles

Individually side panel sections

Co-location

Each section is supplied with its own external security and unique electronic combination

lock systems can be added. These locks can be installed in glass, mesh or solid doors

depending on client specification. The side panels are also supplied with unique locks.




Enclosed cable ducting



Solid floor



Individual lockable side panel sections



Optional solid doors available



Bolted steel frame chassis with high load capacity



Co-Location - enclosures


SPECIFICATION & ORDERING CHART

600mm and 800mm wide enclosures

Product code	U Height	Compartments	Width (mm)	Depth (mm)	Height (mm)
CAB366102PARTCOLO	36	2	600	1000	1970
CAB36882PARTCOLO	36	2	800	800	1970
CAB368102PARTCOLO	36	2	800	1000	1970
CAB42682PARTCOLO	42	2	600	800	2235
CAB426102PARTCOLO	42	2	600	1000	2235
CAB42882PARTCOLO	42	2	800	800	2235
CAB428102PARTCOLO	42	2	800	1000	2235
CAB48682PARTCOLO	48	2	600	800	2505
CAB486102PARTCOLO	48	2	600	1000	2505
CAB48882PARTCOLO	48	2	800	800	2505
CAB488102PARTCOLO	48	2	800	1000	2505



Model shown: CAB42810-4PARTCOLO



Related accessories



Fan units



Compatible shelves



Power distribution units



Cable management

Co-Location - enclosures


SPECIFICATION & ORDERING CHART

600mm and 800mm wide enclosures



Model shown: CAB488104PARTCOLO

Product code	U Height	Compartments	Width (mm)	Depth (mm)	Height (mm)
CAB36684PARTCOLO	36	4	600	800	2025
CAB366104PARTCOLO	36	4	600	1000	2025
CAB36884PARTCOLO	36	4	800	800	2025
CAB368104PARTCOLO	36	4	800	1000	2025
CAB40684PARTCOLO	40	4	600	800	2205
CAB406104PARTCOLO	40	4	600	1000	2205
CAB40884PARTCOLO	40	4	800	800	2205
CAB408104PARTCOLO	40	4	800	1000	2205
CAB48684PARTCOLO	48	4	600	800	2815
CAB486104PARTCOLO	48	4	600	1000	2815
CAB48884PARTCOLO	48	4	800	800	2815
CAB488104PARTCOLO	48	4	800	1000	2815



Goose Grey
RAL 00A05

Black
RAL 9005



Related accessories



Fan units



Cable management



Accessories